

# Pro Pull

INNOVATIVE TOOL FOR FAST AND ACCURATE DENT PULLING

**PRO SPOT**  
QUALITY WELDING SYSTEMS



Pro Spot International, Inc.

Toll Free: 877 PRO SPOT

Fax: (760) 407-1421

E-Mail: [info@prospot.com](mailto:info@prospot.com)

Web: [www.prospot.com](http://www.prospot.com)

## INSTRUCTIONS

ver. 2.0 10/18/2005

# What is in the box:

- \* 1ea. - Pro Pull (PR0-66)
- \* 1ea. - Weld-on shaft (CLP-74)
- \* 2ea. - Contact Tip (CLT-53-8)
- \* 3ea. - Blocking plates (PP-10-01)  
(PP-10-03)  
(PP-10-04)



# Assembly and Welding Instructions:

Pro Pull can be hooked up to most resistance spot welders or dent pullers.  
Welder & Adapters not included.



Pro Pull comes with 3 different Blocking plates with Quick Connect design.

**Block window size:**  
2.5"(63mm) x 1.5"(38mm)  
**PP-10-04**

**Block window size:**  
0.75" (19mm) dia.  
**PP-10-01**

**Block window size:**  
1.75"(44mm) x 1"(25mm)  
**PP-10-03**

Place for different end adapters. Available for most weld guns. (not included) See [prospot.com](http://prospot.com) for more.

**CLT-53-8 8mm Contact Tip**

**N-38 Nut**

**CLP-74**

Removable weld shaft. The weld current is transferred through the shaft and NO CABLE is required to transfer the current

Large openings for great visual control of the pulling area.

1. Attach the weld gun (D) to Weld shaft (C). Secure Lock Bolt (G).
2. Attach desired block plate (A)
3. Position the weld tip in the bottom of the dent, weld it, then pull the handle (F) to initiate the pulling action. **TIP: Use shortest weld TIME possible to prevent extensive weld marks.**

approx. 0.7"(17mm)

**Technical Talk:**

Pro Pull is a unique tool designed to enhance dent repair for the collision industry. Pro Pull does not weld by itself and needs to be hooked up to a power supply such as a resistance welder.

Pro Pull offers advanced features which improve the accuracy and efficiency of dent repair compared to any other systems on the market.

Pro Pull is versatile, its adjustable weld shaft allows the operator flexibility by being able to set the exact distance from the welding tip to the blocking plate.

Pro Pull is equipped with replaceable blocking plates. 3 blocking plates are included with different hole openings.

Depending on the size and nature of the dent you can now focus on the area you want to move during the pull. The blocking plates isolate the area of the metal that moves during the pull.

Pro Pull can be used with any cable spot welders or dent pullers. The weld shaft diameter is 5/8" (16mm) and has a M8 threaded hole at the end of the shaft where adapters can be mounted to fit any brand welders.

**Weight (unit only):** 2.5lb (1.13kg)    **Shipping weight (w/case):** 3.5lb (1.6kg)

**Dimensions (unit only):** 8.5"(216mm) x 1.5"(38mm) x 8.25"(210mm)

**Dimensions (carrying case):** 14"(356mm) x 3.25"(82.6mm) x 10.25"(260mm)

**Weld amperage required:** 1000A minimum

## EASY AS 1 - 2 - 3!

**Aim, position & fire!**

**Pull dent with Auto blocking**

**Twist gun to release... Next...**