




LATERAL TENSION SYSTEM

REDEFINE PANEL REPAIR
WITH CONTROLLED
MECHANICAL PRECISION



MADE IN THE USA



In modern collision repair, efficiency and metal integrity are everything. The Pro Spot Lateral Tension System (LTS) brings controlled mechanical precision directly to your glue-pull and panel repair applications.

By applying a consistent, opposing lateral force, the LTS relieves structural stress, reshapes panels, and drastically reduces repair times. Engineered for seamless integration with glue tabs and adapters, it is the ultimate tool for achieving high-quality, non-invasive cosmetic corrections. Whether you are performing Paintless Dent Repair (PDR) or advanced Glue Pull Repair (GPR), the LTS delivers professional-grade accuracy with zero welding and zero sparks.

KEY BENEFITS & TECHNICAL FEATURES

- **Dual and Single-Action Models:** Select the LTS-SP for swift, single-direction tension, or choose the advanced LTS-DP with dual-pull technology. The dual-pull design creates balanced, opposing forces that distribute stress evenly, preventing glue tabs from "digging in" and causing secondary panel damage.
- **Mechanical Stress Relief:** Unlike aggressive pulling methods, the LTS releases trapped panel tension gently and progressively. This preserves the original metal strength and prevents overstretching.
- **Ultimate Precision Control:** A fine-thread mechanical adjustment mechanism allows technicians to dial in the exact amount of pushing or pulling force required. Perfect for delicate body lines and heavy structural areas alike.
- **Rapid Setup, Zero Prep Sparks:** Because the system relies entirely on glue and mechanical force, there is no need to grind paint, weld pulling pins, or deal with safety hazards like sparks. This makes it 100% paint-safe and incredibly fast to deploy.
- **Heavy-Duty, Lightweight Engineering:** Built from lightweight engineered aluminum, the LTS is designed for daily, heavy-use shop environments while remaining easy to maneuver and fold away.
- **Vertical Mounting System:** Standard kits include two 4.5" heavy-duty suction cups with 100 lbs of strength. Connected via secure nylon lanyards to integrated D-rings on the rail carriage, they anchor the system flush against vertical panels like doors and bedsides.



EFFORTLESS, TOOL-FREE REPOSITIONING



VERSATILE DUAL-DRIVE KNOB



EASY AND FAST INSTALLATION

Image	Model	Description	Application
	LTS-24-SP	24" Single Push/Pull	Ideal for smaller areas such as fenders, etc.
	LTS-24-SP-DX	24" Single Push/Pull Deluxe Version	Ideal for smaller areas such as fenders, etc. Includes additional attachments.
	LTS-36-SP	36" Single Push/Pull	Ideal for quick tension adjustments and repairs.
	LTS-36-SP-DX	36" Single Push/Pull, Deluxe Version	Ideal for quick tension adjustments and repairs. Includes additional attachments.
	LTS-36-DP	36" Dual Push/Pull	For larger or more complex panels requiring balanced opposing force.
	LTS-36-DP-DX	36" Dual Push/Pull Deluxe Version	For larger or more complex panels requiring balanced opposing force. Includes additional attachments.

***LTS-Complete** includes LTS-24-SP-DX, LTS-36-DP-DX, LTS-36-SP-DX

Applications

- Small to medium panel repair
- Glue pull repair (GPR) and paintless dent repair (PDR)
- Structural tension relief on large panels
- Door, Fender, Roof Skins, and Quarter Panel correction
- Stress relieving during repair



PRO SPOT
QUALITY WELDING SYSTEMS



PRO SPOT

QUALITY WELDING SYSTEMS



+1 760-407-1414



5932 Sea Otter Place
Carlsbad, CA 92010



www.PROSPOT.com



info@prospot.com



BRO-LTS Rev. 1.0