


PR-3 Auto **Dent Pulling**

The PR-3 Auto generates precise current and time to prevent damage and corrosion to the backside of the workpiece.

The PR-3 Auto senses when the pull key has made contact with the material and automatically welds the key to the piece being repaired. The Auto feature is very quick and user friendly.



By using weld keys, the user is able to pull a larger area all at once. It is also good for pulling out creases.







Technical Specifications

Input Power: 1 Phase 208-230V or 400V

Input Amperage: 24A

Input Cable: 30' (9m)

Output Amperage: 2,000A Max (at tips)

Welding Cable: 8' (2.5m)

Welding Cable/T-Dent: 8' (2.5m)

Dimensions: 18" x14" x12"

Features:

Auto Weld - Auto senses when a weld tip or pull key makes contact with metal.

The T Dent Handle - Used with the Auto Welding feature. With the turn of the wing nut, all electrodes are compatible with the T Dent Handle. You can also attach slide hammers and Pro Spot's Pro Pull to maximize dent pulling.

Single Sided Welding - 10 different Single-Sided welding applications give you the power and versatility to complete any job.

Single-Sided Welding

The PR-3 Auto is capable of handling a variety of single-sided welding needs which include: washer, nut & bolt, nail, rivet and stitch.






760-407-1414



info@prospot.com



www.prospot.com



Pro Spot International, Inc. U.S.A. 5932 Sea Otter Place Carlsbad, CA 92010