

Material Safety Data Sheet

NAME OF ITEM:

**Li-ion BATTERY PACK
p/n: PRR-21**

1. Chemical product identification

Name of Items	Li-ion BATTERY PACK
Type/Model	TL-MAK-18B-3.0Ah
Rated capacity	3000mAh
Nominal voltage	18V
Rated energy	54Wh
Inspection according to	EEC Directive 93/112/EC UN "Recommendations on the TRANSPORT OF DANGEROUS GOODS"
Emergency telephone call	Mr. Liu 18129946709

2. Composition information

Material or ingredient	CAS No.	Wt %
Lithium Co Mn Oxid	/	39.6
Polyvinylidene Fluoride	24937-79-9	1.15
Aluminium	7429-90-5	5.56
Graphite	7782-42-5	23.2
Styrene-Butadiene Rubber	9003-55-8	1.78
Copper	7440-50-8	9.80
Lithium Hexafluorophosphate	21324-40-3	15.35
Polyethylene	9002-88-4	0.06
Polyethylene	9003-07-0	0.78
Electrolyte Carbonate	96-49-1	2.72

3. Hazards identification	
Explosive risk	This article does not belong to the explosion dangerous goods.
Flammable risk	This article does not belong to the flammable material.
Oxidation risk	This article does not belong to the oxidation of dangerous goods.
Toxic risk	This article does not belong to the toxic dangerous goods.
Radioactive risk	This article does not belong to the radiation of dangerous goods.
Mordant risk	This article does not belong to the corrosion of dangerous goods.
Other risk	This article is Li-ion BATTERY PACK, Watt hour 54 Wh, which belong to the Li-ion battery.

4. First aid measures

Eye: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Skin: Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes.
Get medical aid.

Inhalation: Remove from exposure and move to fresh air immediately. Use oxygen if available.

Ingestion: Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious.
Call a physician.

5. Fire-fighting measures

Flash Point: N/A.

Auto-ignition Temperature: N/A.

Extinguishing Media: Water, CO2.

Special Fire-Fighting Procedures: Self-contained breathing apparatus.

Unusual Fire and Explosion Hazards: Cell may vent when subjected to excessive heat-exposing battery contents.

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

6. Accidental release measures

Steps to be taken in case Material is Released or Spilled

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the battery to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

Waste Disposal Method

It is recommended to discharge the battery to the end, to use up the metal lithium inside the battery, and to bury the discharged battery in soil.

7. Handling and storage

The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.

Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

Other Precautions

The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

8. Exposure controls/personal protection

Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use.

Ventilation

Not necessary under conditions of normal use.

Protective Gloves

Not necessary under conditions of normal use.

Other Protective Clothing or Equipment

Not necessary under conditions of normal use.

Personal Protection is recommended for venting battery

Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

9. Physical and chemical properties

Appearance: Prismatic.

Odor: Under normal circumstances, is odorless; if leaking, smells of medical ether.

pH: Not applicable as supplied.

Flash Point: Not applicable unless individual components exposed.

Flammability: Not applicable unless individual components exposed.

Relative density: Not applicable unless individual components exposed.

Solubility (water): Not applicable unless individual components exposed.

Solubility (other): Not applicable unless individual components exposed.

10. Stability and reactivity

Stability: Product is stable under conditions described in Section 7.

Conditions to Avoid : Heat above 70°C or incinerate. Deform. Mutilate. Crush. Disassemble.

Overcharge. Short circuit. Expose over a long period to humid conditions.

Materials to avoid: Oxidizing agents, alkalis, water.

Hazardous Decomposition Products : Toxic Fumes, and may form peroxides.

Hazardous Polymerization : N/A.

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated hydrocarbons.

11. Toxicological information

Signs & symptoms: None, unless battery ruptures.

In the event of exposure to internal contents, vapor fumes may be very irritating to the eyes and skin.

Inhalation: Lung irritant.

Skin contact: Skin irritant.

Eye contact: Eye irritant.

Ingestion: Poisoning if swallowed.

Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, moderate to severe irritation, burning and dryness of the skin may occur, Target organs nerves, liver and kidneys.

12. Ecological information

Eco-toxicity: None known at present.

Bioaccumulation potential: Slowly Bio-degradable.

Environmental fate: None known environmental hazards at present.

13. Disposal consideration

Do not incinerate, or subject cells to temperature in excess of 70°C, Such abuse can result in loss of seal leakage, and/or cell explosion. Dispose of in accordance with appropriate local regulations.

14. Transport information

Scope of application: This report applies to by sea, by air, and by land.

Label for conveyance: Class 9 hazard label.

UN Number: UN3480.

Packaging Group: N/A.

EmS No: F-A ,S-I.

EmS 编号: F-A ,S-I。

Marine pollutant: No

Proper Shipping name : Li-ion BATTERY PACK.

Hazard Classification: The goods shall be complied with the requirements of Packing Instructions

952 of 60th DGR Manual of IATA(2019 edition)or special provision 188 of IMDG CODE(Amdt. 39-18)2018 Edition, including the passing of the UN38.3 test.

15. Regulation information

Law information

《Dangerous Goods Regulations》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods》

《Occupational Safety and Health Act》 (OSHA)

《Toxic Substance Control Act》 (TSCA)

《Consumer Product Safety Act》 (CPSA)

《Federal Environmental Pollution Control Act》 (FEPCA)

《The Oil Pollution Act》 (OPA)

《Superfund Amendments and Reauthorization Act Title III
(302/311/312/313)》 (SARA)

《Resource Conservation and Recovery Act》 (RCRA)

《Safety Drinking Water Act》 (CWA)

《California Proposition 65》

《Code of Federal Regulations》 (CFR)

In accordance with all Federal, State and local laws.

-----END-----